

Conectores

Voltagem Máxima: 105°C 300 Volts



Conector Rosqueado com Mola Metálica

	Bitola mm ²	Código	Dimensões		
			A	B	C
	0,84 - 2,62mm ²	WN1	15,2	8,6	6,7
	1,55 - 3,93mm ²	WN2	17,6	9,8	7,4
	1,55 - 4,75mm ²	WN3	22,0	12,0	9,9
	2,90 - 9,14mm ²	WN4	24,5	14,0	11,0
	4,16 - 17,13mm ²	WN6	27,4	16,8	12,7
	9,93 - 21,04mm ²	WN8	32,2	18,3	12,8

Conectores para Fechar Ponta



Bitola mm ²	Código	Dimensões					Alicate para Crimpagem
		W	F	L	D	T	
1,25 mm ²	CE1	5,3	8,0	21,0	9,8	0,5	KS-KST2000G
2 mm ²	CE2	6,0	9,0	21,0	10,0	0,5	
5,5 mm ²	CE5	7,6	10,0	25,5	12,5	0,7	
8 mm ²	CE8	10,0	11,0	29,8	14,4	1,25	

Conectores para Fechar Ponta (Cabeça Plana)



Bitola mm ²	Código	Dimensões					Alicate para Crimpagem
		W	F	L	D	T	
1,25 mm ²	PB1	5,3	6,2	15,2	8,0	0,5	KS-KST2000G
2 mm ²	PB2	6,0	6,2	15,2	8,3	0,5	
5,5 mm ²	PB5	7,6	8,3	17,8	11,2	0,7	
8 mm ²	PB8	10,0	8,85	22,0	14,2	1,25	