



Engates de Isolação PVC 0,5 - 6 mm²

Corrente Máxima:

10 Amp
 15 Amp
 24 Amp

Voltagem Máxima: 75°C 300 Volts
Isolação: PVC

Liga de Cobre



Macho

	Bitola mm ²	Código	Nema Tab	Dimensões				Alicate para Crimpagem
				W	F	L	D	
	0,5 - 1,5 mm ²	MDV1-110-5 MDV1-110-8	(0,5 X 2,8) (0,8 X 2,8)	2,8	6,5	18,5	4,0	OT-SN-03C KS-JD-90512
	0,5 - 1,5 mm ²	MDV1-250	(0,8 X 6,35)	6,35	7,7	21,0	4,0	
	1,5 - 2,5 mm ²	MDV2-250	(0,8 X 6,35)	6,35	7,7	21,0	4,5	
	4 - 6 mm ²	MDV5-250	(0,8 X 6,35)	6,35	7,7	24,0	5,5	



Fêmea Totalmente Isolado

	Bitola mm ²	Código	Nema Tab	Dimensões				Alicate para Crimpagem
				W	F	L	D	
	0,5 - 1,5 mm ²	FDFV1-187-5 FDFV1-187-8	(0,5 X 4,75) (0,8 X 4,75)	5,0	6,4	19,3	4,0	OT-SN-03C KS-JD-90512
	0,5 - 1,5 mm ²	FDFV1-250	(0,8 X 6,35)	6,6	7,3	22,0	4,0	
	1,5 - 2,5 mm ²	FDFV2-110-5 FDFV2-110-8	(0,5 X 2,8) (0,8 X 2,8)	5,0	6,4	19,3	4,0	
	1,5 - 2,5 mm ²	FDFV2-187-5 FDFV2-187-8	(0,5 X 4,75) (0,8 X 4,75)	5,0	6,4	19,3	4,5	
	1,5 - 2,5 mm ²	FDFV2-250	(0,8 X 6,35)	6,6	7,3	22,0	4,5	
	4 - 6 mm ²	FDFV5-250	(0,8 X 6,35)	6,6	7,3	24,3	5,5	

MDV1-110-5



MDV1-110-8



MDV1-250



MDV2-250



MDV5-250



FDFV2-110-8



FDFV2-187-8



FDFV1-250



FDFV2-250



FDFV5-250

