



Engates Totalmente Isolados NYLON 0,5 - 6 mm²

Corrente Máxima:

10 Amp

15 Amp

24 Amp

Voltagem Máxima: 105°C 300 Volts

Isolação: NYLON

Liga de Cobre



Fêmea

	Bitola mm ²	Código	Nema Tab	Dimensões				Alicate para Crimpagem
				W	F	L	D	
	0,5 - 1,5 mm ²	FDFN1-250-CLEAR	(0,8 X 6,35)	6,6	7,3	22,0	4,0	OT-SN-03C KS-JD-90512
	1,5 - 2,5 mm ²	FDFN2-250-CLEAR	(0,8 X 6,35)	6,6	7,3	22,0	4,5	
	4 - 6 mm ²	FDFN5-250	(0,8 X 6,35)	6,6	7,3	24,0	6,3	
	0,5 - 1,5 mm ²	FDFNY1-250	(0,8 X 6,35)	6,6	7,3	22,5	4,0	
	1,5 - 2,5 mm ²	FDFNY2-250	(0,8 X 6,35)	6,6	7,3	23,0	4,5	
	4 - 6 mm ²	FDFNY5-250	(0,8 X 6,35)	6,6	7,3	24,5	5,0	

Macho

	Bitola mm ²	Código	Nema Tab	Dimensões				Alicate para Crimpagem
				W	F	L	D	
	0,5 - 1,5 mm ²	MDFN1-250	(0,8 X 6,35)	6,35	7,7	24,0	4,0	OT-SN-03C KS-JD-90512
	1,5 - 2,5 mm ²	MDFN2-250	(0,8 X 6,35)	6,35	7,7	24,0	4,5	
	4 - 6 mm ²	MDFN5-250	(0,8 X 6,35)	6,35	7,7	25,0	6,3	
	0,5 - 1,5 mm ²	MDFNY1-250	(0,8 X 6,35)	6,35	7,7	24,5	4,0	
	1,5 - 2,5 mm ²	MDFNY2-250	(0,8 X 6,35)	6,35	7,7	24,5	4,5	
	4 - 6 mm ²	MDFNY5-250	(0,8 X 6,35)	6,35	7,7	26,0	5,0	

FDN1-250-CLEAR



FDN2-250-CLEAR



FDN5-250



FDNY5-250



MDFN1-250



MDFN2-250



MDFN5-250



MDFNY5-250

