

Anel Pré-Isolado 0,5 - 2,5 mm²

Corrente Máxima:

18 Amp

30 Amp

Voltagem Máxima:


105°C 600 Volts

Isolação:

PVC

Cobre Eletrolítico

99,95%



PRÉ-ISOLADO - RV

NÃO-ISOLADO - RN

REFORÇADO - RD

Bitola mm ²	Código	Furo D2	Dimensões			Alicate para Crimpagem
			W	L	L1	
0,5 - 1,5 mm ²	RV1-3.2	#4	3.20	5.50	1750	15.0
	RVS1-3.7	#6	3.70	5.50	1750	15.0
	RVM1-3.7	#6	3.70	6.60	1940	16.3
	RVL1-3.7	#6	3.70	8.0	2080	17.0
	RVS1-4	#8	4.30	6.60	1940	16.3
	RVL1-4	#8	4.30	8.0	2080	17.0
	RV1-5	#10	5.30	8.0	2080	17.0
	RV1-6	1/4	6.40	7.20	2680	21.0
	RV1-8	5/16	8.40	9.50	2680	21.0
	RV1-10	3/8	10.5	9.50	3050	23.9
1,5 - 2,5 mm ²	RVS2-3.7	#6	3.70	6.60	1780	14.8
	RVM2-3.7	#6	3.70	6.60	1940	16.3
	RVL2-3.7	#6	3.70	8.50	1940	17.8
	RVS2-4	#8	4.30	6.60	2080	16.3
	RVL2-4	#8	4.30	8.50	2180	17.8
	RVS2-5	#10	5.30	8.50	2180	17.8
	RVL2-5	#10	5.30	9.50	2180	17.3
	RV2-6	1/4	6.40	12.0	2680	21.0
	RV2-8	5/16	8.40	12.0	2680	21.0
	RV2-10	3/8	10.5	13.6	3050	23.9

Pré-isolado:

OT-SN-03C
KS-JD-90512

Sem-isolação:

OT-SN-06
OT-BN-16
KS-JD-90512

RV1-3.2
RD1-3.2
RN1-3.2



RVS1-3.7
RDS1-3.7
RNS1-3.7



RVM1-3.7
RDM1-3.7
RNM1-3.7



RVL1-3.7
RDL1-3.7
RNL1-3.7



RVS1-4
RDS1-4
RNS1-4



RVL1-4
RDL1-4
RNL1-4



RV1-5
RD1-5
RN1-5



RV1-6
RD1-6
RN1-6



RV1-8
RD1-8
RN1-8



RV1-10
RD1-10
RN1-10



RVS2-3.7
RDS2-3.7
RNS2-3.7



RVM2-3.7
RDM2-3.7
RNM2-3.7



RVL2-3.7
RDL2-3.7
RNL2-3.7



RVS2-4
RDS2-4
RNS2-4



RVL2-4
RDL2-4
RNL2-4



RVS2-5
RDS2-5
RNS2-5



RVL2-5
RDL2-5
RNL2-5



RV2-6
RD2-6
RN2-6



RV2-8
RD2-8
RN2-8



RV2-10
RD2-10
RN2-10



* Tamanho na proporção 1:1