



# Detailed information for: C2SS1-10B-11

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

# C2SS1-10B-11

## General Information

<b>Extended Product Type:</b>	C2SS1-10B-11
<b>Product ID:</b>	1SFA619200R1076
<b>EAN:</b>	7320500245491
<b>Catalog Description:</b>	SELECTOR SWITCH#C2SS1-10B-11
<b>Long Description:</b>	Compact Selector Switch - 2-pos Fixed B&C - Short handle - Black - Non-illuminated - Black plastic - 1NO+1NC

## Categories

Products » Low Voltage Products and Systems » Control Products » Pilot Devices » Pilot Devices - Compact Range

## Ordering

<b>EAN:</b>	7320500245491
<b>Minimum Order Quantity:</b>	10 piece
<b>Customs Tariff Number:</b>	85369001

## Dimensions

<b>Product Net Width:</b>	0.030 m
<b>Product Net Height:</b>	0.030 m
<b>Product Net Depth:</b>	0.072 m
<b>Product Net Weight:</b>	0.024 kg

## Container Information

<b>Package Level 1 Units:</b>	10 piece
<b>Package Level 1 Width:</b>	0.1 m
<b>Package Level 1 Height:</b>	0.03 m
<b>Package Level 1 Length:</b>	0.1 m
<b>Package Level 1 Gross Weight:</b>	0.024 kg
<b>Package Level 2 Units:</b>	10

## Environmental

<b>Ambient Air Temperature:</b>	Storage -30 ... +85 °C Operation -25 ... +70 °C
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Additional Information

<b>Actuator Type:</b>	Short handle
<b>Bezel Material:</b>	Black plastic
<b>Block:</b>	1NO+1NC
<b>Color:</b>	Black
<b>Degree of Protection:</b>	Front IP69K Terminals IP20
<b>Function:</b>	Maintained

<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Illumination:</b>	Non-illuminated
<b>Maintained Positions:</b>	B, C
<b>Mechanical Durability:</b>	0.5 million
<b>Number of Auxiliary Contacts NC:</b>	1
<b>Number of Auxiliary Contacts NO:</b>	1
<b>Product Main Type:</b>	C2SS1
<b>Product Name:</b>	Selector Switch
<b>Product Range:</b>	Compact
<b>Product Type:</b>	C2SS
<b>Rated Frequency (f):</b>	Supply Circuit 60 Hz Supply Circuit 50 Hz
<b>Rated Operational Current AC-15 (I<sub>e</sub>):</b>	(24 / 127 V) 1.5 A (220 / 240 V) 1 A
<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(24 V) 0.3 A (125 V) 0.2 A
<b>RoHS Date:</b>	0626 5
<b>Sub-Function:</b>	2-position

## Certificates and Declarations (Document Number)

**Data Sheet, Technical Information:** [1SFC151005C0201](#)

**Declaration of Conformity - CE:** [1SFA1-70](#)

**Environmental Information:** [1SFC151009D0201](#)

**Instructions and Manuals:** [1SFC151005C0201](#)

**RoHS Information:** [1SFC151012D0202](#)

## Classifications

<b>E-nummer:</b>	3711300
<b>ETIM 4:</b>	EC002024 - Accessories for control circuit devices
<b>ETIM 5:</b>	EC001029 - Selector switch, complete
<b>ETIM 6:</b>	EC001029 - Selector switch, complete
<b>Object Classification Code:</b>	S
<b>UNSPSC:</b>	39121500



---

© Copyright 2018 ABB