


PRODUCT-DETAILS

BEA26-4

BEA26-4 Connecting Link with Manual Motor Starter



General Information

| | |
|-----------------------|---|
| Extended Product Type | BEA26-4 |
| Product ID | 1SBN082306T1000 |
| EAN | 3471523130746 |
| Catalog Description | BEA26-4 Connecting Link with Manual Motor Starter |

| | |
|------------------|--|
| Long Description | <p>Connecting links with manual motor starters</p> <p>The BEA insulated 3-pole connecting links are used to connect AF09 ... AF65 contactors with the MS116 or MS132 or MS165 manual motor starters. The BEA insulated 3-pole connecting links ensure the electrical and mechanical connection between the contactor and the associated manual motor starter. BPR65-4 35 mm rail hooks used with BEA65-4 connecting link, allow direct mounting on 2 rails 35 mm of MS165 manual motor starters with AF40 ... AF65 contactors.</p> |
|------------------|--|

Ordering

| | |
|------------------------|---------------|
| E-Number (Sweden) | 3211493 |
| EAN | 3471523130746 |
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85389099 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 45 mm |
| Product Net Height | 41.8 mm |
| Product Net Depth / Length | 48 mm |

| | |
|--------------------|----------|
| Product Net Weight | 0.025 kg |
|--------------------|----------|

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 10 piece |
| Package Level 1 Width | 100 mm |
| Package Level 1 Height | 64 mm |
| Package Level 1 Depth / Length | 187 mm |
| Package Level 1 Gross Weight | 0.25 kg |
| Package Level 1 EAN | 3471523130746 |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Additional Information

| | |
|--------------------|--|
| Medium Description | BEA26-4 Connecting Link is used to connect AF26..AF38 contactors with the MS116-0,16 ... MS116-16 or MS132-0,16 ... MS132-10 manual motor starters. The BEA insulated 3-pole connecting links ensure the electrical and mechanical connection between the contactor and the associated manual motor starter. |
| Order Multiple | 10 piece |
| Product Main Type | Accessories for Block Contactors |
| Product Name | Connecting Link |
| RoHS Date | 20171115 |
| Suitable For | AF26 AF30 AF38 MO132 MS116 MS132 |
| Terminal Type | Screw Terminals |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------------------|
| Declaration of Conformity - CE | 1SBD250021U1000 |
| Environmental Information | 1SBD250188E1000 |
| GOST Certificate | GOST_POCCFR.ME77.B07175.pdf |
| Instructions and Manuals | 1SBC101030M6801 |
| RINA Certificate | RINA_ELE084013XG |
| RoHS Information | 1SBD250021U1000 |
| UL Certificate | UL_20120730-E312527 |
| UL Listing Card | UL_E312527 |

Classifications

| | |
|--------|--|
| ETIM 4 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 5 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 6 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 7 | EC002498 - Accessories for low-voltage switch technology |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

