

PRODUCT-DETAILS

# PSR30-600-70

## PSR30-600-70 Softstarter



### General Information

Global Commercial Alias	PSR30-600-70
Extended Product Type	PSR30-600-70
Product ID	1SFA896109R7000
ABB Type Designation	PSR30-600-70
EAN	7320500338308
Catalog Description	PSR30-600-70 Softstarter
Long Description	Softstarter PSR30-600-70 for max 600V main voltage and 100-240V 50/60Hz control supply voltage

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85044090

### Popular Downloads

Data Sheet, Technical Information	1SFC132005C0201
Instructions and Manuals	1SFC132031M0001

### Dimensions

Product Net Width	128 mm
Product Net Height	160 mm
Product Net Depth / Length	45 mm
Product Net Weight	0.6 kg

## Technical

Rated Operational Voltage	208 ... 600 V AC
Rated Control Supply Voltage (U <sub>s</sub> )	100 ... 240 V AC
Rated Control Circuit Voltage (U <sub>c</sub> )	50 Hz / 60 Hz 100 ... 240 V AC
Rated Frequency (f)	50/60 Hz Main Circuit 50/60 Hz
Rated Operational Power - In-Line Connection (P <sub>e</sub> )	(230 V) 7.5 kW (400 V) 15 kW (500 V) 18.5 kW
Rated Operational Current - In-Line Connection (I <sub>e</sub> )	30 A
Service Factor Percentage	100 %
Overload Protection	Recommended MS132 25 ... 32
Integrated Electronic Overload	No
Adjustable Rated Motor Current I <sub>e</sub>	No
Starting Capacity at Maximum Rated Current I <sub>e</sub>	4xI <sub>e</sub> for 6s
Ramp Time	0 ... 20 second [unit of time] 1 ... 10 second [unit of time]
Initial Voltage During Start	40 ... 70 %
Step Down Voltage Special Ramp	100 ... 60 %
Current Limit Function	No
Switch for Inside Delta Connection	No
Run Signal Relay	Yes
By-pass Signal Relay	Yes
Fault Signal Relay	No
Overload Signal Relay	No
Signal indication completed start ramp (LED)	Green
Signal indication ready to start/standby ON (LED)	Green
Signal indication running R (LED)	Green
Signal indication ramping up/down (LED)	Green
Number of Starts Per Hour at 3.5*I <sub>e</sub> for 7 sec. 50% ON Time 50% OFF Time	10
Communication	FiledBusPlug(Optional)
Degree of Protection	IP20
Terminal Type	Screw Terminals
Connecting Capacity	Rigid 1/2 x 2.5 ... 10 mm <sup>2</sup>

Main Circuit	
Connecting Capacity Control Circuit	Rigid 1 x 0.75 ... 2.5 mm <sup>2</sup> Rigid 2 x 0.75 ... 1.5 mm <sup>2</sup>
Connecting Capacity Supply Circuit	Rigid 1 x 0.75 ... 2.5 mm <sup>2</sup>
Tightening Torque	Control Circuit 0.6 N·m Main Circuit 2.3 N·m Supply Circuit 0.6 N·m
Product Main Type	PSR30

## Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +70 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Certificates and Declarations (Document Number)

CQC Certificate	CQC2006010304208086
Declaration of Conformity - CCC	2020980304001088
Declaration of Conformity - CE	1SFA1-90
Environmental Information	1SFC132038D0201
Instructions and Manuals	1SFC132031M0001
RoHS Information	1SFC132031D0202

## Container Information

Package Level 1 Width	137 mm
Package Level 1 Depth / Length	50 mm
Package Level 1 Height	176 mm
Package Level 1 Gross Weight	0.7 kg
Package Level 1 EAN	7320500338308
Package Level 1 Units	box 1 piece

## Classifications

Object Classification Code	Q
ETIM 4	EC002572 - Electronic motor control and protection device
ETIM 5	EC002572 - Electronic motor control and protection device
ETIM 6	EC002572 - Motor management device
UNSPSC	39121521

## Categories

Drives → Softstarters → Softstarters → PSR Softstarters → PSR30

Low Voltage Products and Systems → Control Products → Softstarters → Softstarters → PSR Softstarters → PSR30

