



### Engates de Isolação PVC 0,5 - 6 mm<sup>2</sup>

Corrente Máxima:

10 Amp   
  13 Amp  
 24 Amp

Voltagem Máxima: 75°C 300 Volts

Isolação: PVC

Liga de Cobre

### Fêmea



	Bitola mm <sup>2</sup>	Código	Nema Tab	Dimensões				Alicate para Crimpagem
				W	F	L	D	
	0,5 - 1,5 mm <sup>2</sup>	FDV1-110-5 FDV1-110-8	(0,5 X 2,8) (0,8 X 2,8)	3,2	6,5	18,6	4,0	OT-SN-03C KS-JD-90512
	0,5 - 1,5 mm <sup>2</sup>	FDV1-187-5 FDV1-187-8	(0,5 X 4,75) (0,8 X 4,75)	5,0	6,4	18,0	4,0	
	0,5 - 1,5 mm <sup>2</sup>	FDV1-205-8	(0,8 X 5,20)	6,6	7,3	20,5	4,0	
	0,5 - 1,5 mm <sup>2</sup>	FDV1-250	(0,8 X 6,35)	6,6	7,3	20,5	4,0	
	1,5 - 2,5 mm <sup>2</sup>	FDV2-110-5 FDV2-110-8	(0,5 X 2,8) (0,8 X 2,8)	3,2	6,5	18,6	4,5	
	1,5 - 2,5 mm <sup>2</sup>	FDV2-187-5 FDV2-187-8	(0,5 X 4,75) (0,8 X 4,75)	5,0	6,4	18,0	4,5	
	1,5 - 2,5 mm <sup>2</sup>	FDV2-205-5	(0,5 X 5,20)	6,6	7,3	20,5	4,0	
	1,5 - 2,5 mm <sup>2</sup>	FDV2-205-8	(0,8 X 5,20)	6,6	7,3	20,5	4,0	
	1,5 - 2,5 mm <sup>2</sup>	FDV2-250	(0,8 X 6,35)	6,6	7,3	20,5	4,5	
	1,5 - 2,5 mm <sup>2</sup>	FDV2-312	(0,8 X 8,0)	8,2	4,0	24,2	4,5	
	4 - 6 mm <sup>2</sup>	FDV5-187-8	(0,8 X 4,75)	5,0	6,5	22,0	5,5	
	4 - 6 mm <sup>2</sup>	FDV5-250	(0,8 X 6,35)	6,6	7,3	23,5	5,5	

FDV1-110-5



FDV1-110-8



FDV1-187-8



FDV1-205-8



FDV2-110-8



FDV2-187-8



FDV2-205-5



FDV2-205-8



FDV5-187-8



FDV1-250



FDV2-250



FDV5-250

