http://new.abb.com/products/1SFA619402R1002?printPreview

Detailed information for: CL-100G

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

CL-100G

| General Information | |
|----------------------------------|--|
| Extended Product Type: | CL-100G |
| Product ID: | 1SFA619402R1002 |
| EAN: | 7320500204122 |
| Catalog Description: | PILOT LIGHT#CL-100G |
| Long Description: | Compact Pilot Light - Pilot light head - Green - Illuminated - Lamptype: Ba9s |
| Categories | |
| • | oducts and Systems » Control Products » Pilot Devices » Pilot |
| Ordering | |
| EAN: | 7320500204122 |
| Minimum Order Quantity: | 10 piece |
| Customs Tariff Number: | 85369001 |
| | |
| Dimensions | |
| Product Net Width: | 0.030 m |
| Product Net Height: | 0.030 m |
| Product Net Depth: | 0.055 m |
| Product Net Weight: | 0.018 kg |
| Container Information | |
| Package Level 1 Units: | 10 piece |
| Package Level 1 Width: | 0.1 m |
| Package Level 1 Height: | 0.03 m |
| Package Level 1 Length: | 0.1 m |
| Package Level 1 Gross Weight: | 0.018 kg |
| Package Level 2 Units: | 10 |
| Environmental | |
| Ambient Air Temperature: | Storage -30 +85 °C Operation -25 +70 °C |
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| Additional Information | |
| Actuator Type: | Pilot light head |
| Bezel Material: | N/A |
| Color: | Green |
| Degree of Protection: | Front IP69K |
| | Terminals IP20 |
| IIT Publishing Status: | Level 0 - Information enabled |
| Illumination: | Illuminated |
| | |

27/02/2018

| Lamp Type: | Ba9s | |
|---|--|--|
| Lens Color: | Green | |
| Product Main Type: | CL | |
| Product Name: | Pilot Light | |
| Product Range: | Compact | |
| Product Type: | CL | |
| Rated Control Supply Voltage (U _s): | 240 V | |
| Rated Frequency (f): | Supply Circuit 60 Hz Supply Circuit 50 Hz | |
| Rated Operational Current AC-15 (I _e): | (24 / 127 V) 1.5 A (220 / 240 V) 1 A | |
| Rated Operational Current DC-13 (I _e): | (24 V) 0.3 A (125 V) 0.2 A | |
| RoHS Date: | 0626 5 | |
| Suitable For: | Bulb 3W max. | |
| Certificates and Declarations (Document Number) | | |
| Data Sheet, Technical Information: | <u>1SFC151005C0201</u> | |
| Declaration of Conformity CE: | - <u>1SFA1-70</u> | |
| Environmental Information: | <u>1SFC151009D0201</u> | |
| Instructions and Manuals: | <u>1SFC151005C0201</u> | |
| RoHS Information: | 1SFC151012D0202 | |
| Classifications | | |
| E-nummer: | 3711202 | |
| ETIM 4: | EC002024 - Accessories for control circuit devices | |
| ETIM 5: | EC000272 - Indicator light complete | |
| ETIM 6: | EC000272 - Indicator light complete | |
| Object Classification Code: E | | |
| UNSPSC: | 39121500 | |



© Copyright 2018 ABB